



Building Solutions

Ceramic tile adhesives
and grouts, waterproofing
and repair products

info@constructionchemicals.com.au
www.constructionchemicals.com.au

Adelaide

49-57 Davis St
Wingfield SA 5013
Phone (08) 8243 7888
Fax (08) 8243 7800

Brisbane

45 Coulson St
Wacol QLD 4076
Phone (07) 3271 2944
Fax (07) 3271 3892

Darwin

4/4 Aristos Pl
(off Farrell Cres)
Winnellie NT 0820
Phone (08) 8947 1811
Fax (08) 8947 1819

Melbourne

11 Gabrielle Ct
Bayswater North VIC 3153
Phone (03) 9761 4711
Fax (03) 9761 4748

Perth

11 Collie St
Welshpool WA 6106
Phone (08) 9356 9999
Fax (08) 9356 9955

Sydney

31-33 Newton Rd
Wetherill Park NSW 2164
Phone (02) 9756 3533
Fax (02) 9756 3534

Auckland

16 Carpenter Rd
East Tamaki
Phone (09) 273 5444
Fax (09) 273 5442

Kuala Lumpur

Lot 2 Jalan Kecapi
33/2 Elite Industrial Estate
Off Jalan Bukit Kemuning
40000 Shah Alam
Phone (603) 5122 2522
Fax (603) 5122 2526

MATERIAL SAFETY DATA SHEET

Issued: 09/10/2000
Revised: 01/07/2010
Code: Amber

IDENTIFICATION

Product Name: **BLOKBOND**
UN Number: None Allocated
Dangerous Goods Class: None Allocated
Subsidiary Risk Class: Not Listed
Hazchem Code: None Allocated
Packaging Group: None Allocated
Poisons Schedule: None Allocated
Use: A cement based ceramic tile adhesive.

Not classified as hazardous according to criteria of Worksafe Australia.

Physical Description/Properties

Appearance: A light coloured finely divided cement type powder
Boiling Point (°C): Not Applicable
Vapour Pressure (kPa): Not Applicable
Specific Gravity: 3
Flash Point (°C): Not applicable
Flammability Limits: Not applicable
Solubility in Water: Only slight

Ingredients

Proprietary blend of Cement, Sand, Inorganic fillers and ingredients determined not hazardous.

Caution: contains cement which contains silica

HEALTH HAZARD INFORMATION

Health Effects

Swallowed - Classified as an inert nuisance dust. Exposure can irritate skin, eyes and mucous membrane.

Eye - In dust form may cause inflammation of the cornea.

Skin - Irritant when wet, which can dry the skin and cause alkali burns. Slight possibility of causing dermatitis.

Inhaled - As a dust can irritate mucous membrane.

First Aid

Swallowed - Wash mouth and lips with water and seek medical attention

Eye - Irrigate with copious quantities of water. If soreness or redness persists, seek medical attention.

Skin - Wash off with tepid soap and water. Remove contaminated clothing and launder before re-use.

Inhalation - Move to fresh air, wash with water and seek medical attention if effects persist.

PRECAUTIONS FOR USE

Exposure Limits - Classified as an inert nuisance dust.

Ventilation - Where practical, suitable means of dust extraction should be applied as necessary to maintain acceptable levels. Persons with a history of respiratory illness or reduced pulmonary function should avoid work places with high dust levels.

Personal Protection - In dusty environments, the use of filter masks complying with AS1716 (class L) and tight fitting goggles is advised. Use of barrier creams or impervious gloves, boots and clothing to protect skin from contact with dust and wet product is recommended.

Flammability - Blokbond is not combustible.

SAFE HANDLING INFORMATION

Storage and Transport - Product should be stored in a dry place and protected from ingress of moisture, as this will cause it to harden in storage.

Spills and Disposal - Spills may be cleaned up by any dry method such as broom, shovel or vacuum device. Take care to minimize dust. Clean up personnel should wear full cover clothing, gloves, boots, dust masks and goggles.

Fire/Explosion Hazard - Blokbond poses no hazard.

All information in this data sheet is as accurate and up-to-date as possible. Since Construction Chemicals cannot anticipate or control the conditions under which this information may be used, each user should review the information in the specific context of the intended application. Construction Chemicals will not be responsible for damages of any nature resulting from use of or reliance upon the information.