SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product nameRAPIDFIX LIQUIDSynonym(s)TRADEMASTIC

1.2 Uses and uses advised against

Use(s) TILE ADHESIVE

1.3 Details of the supplier of the product

Supplier name	DRIBOND CONSTRUCTION CHEMICALS
Address	49-57 Davis Street, Wingfield, SA, 5013, AUSTRALIA
Telephone	(08) 8243 7888
Fax	(08) 8243 7800
Email	info@constructionchemicals.com.au
Website	www.constructionchemicals.com.au

1.4 Emergency telephone number(s)

Emergency

(08) 8243 7888

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

2.2 Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
ACRYLIC EMULSION	-	-	<100%
ADDITIVE(S)	-	-	<100%
WATER	7732-18-5	231-791-2	<100%
FILLER(S)	-	-	<100%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Еуе	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

ChemAlert.

Skin

PRODUCT NAME RAPIDFIX LIQUID

IngestionFor advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once).

First aid facilities No information provided.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve carbon oxides and hydrocarbons when heated to decomposition.

5.3 Advice for firefighters

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

No exposure standards have been entered for this product.

Biological limits

No biological limit values have been entered for this product.



8.2 Exposure controls

Engineering controls

controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

PPE

Eye / Face	Wear splash-proof goggles.
Hands	Wear PVC or rubber gloves.
Body	When using large quantities or where heavy contamination is likely, wear coveralls.
Respiratory	If sanding dry product, wear a Class P1 (Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	WHITE LIQUID
Odour	SLIGHT AMMONIACAL ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	100°C (Approximately)
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
рН	NOT AVAILABLE
Vapour density	NOT AVAILABLE
Specific gravity	1.0
Solubility (water)	SOLUBLE
Vapour pressure	2.3 kPa @ 20°C
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites) and acids (e.g. nitric acid).

10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	Information available for the product: This product is expected to be of low toxicity. Based on available data, the classification criteria are not met.
Skin	Not classified as a skin irritant. Prolonged or repeated contact may result in mild irritation, rash and dermatitis.
Eye	Not classified as an eye irritant. Contact may result in mild irritation, lacrimation and redness.
Sensitisation	Not classified as causing skin or respiratory sensitisation.
Mutagenicity	Not classified as a mutagen.
Carcinogenicity	Not classified as a carcinogen.
Reproductive	Not classified as a reproductive toxin.
STOT – single exposure	Not classified as causing organ damage from single exposure. However, high level exposure may result in dizziness, nausea and headache.
STOT – repeated exposure	Not classified as causing organ damage from repeated exposure.
Aspiration	Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposalFor small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site.
Contact the manufacturer/supplier for additional information if disposing of large quantities (if required).

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None Allocated	None Allocated	None Allocated
14.2 Proper Shipping Name	None Allocated	None Allocated	None Allocated
14.3 Transport Hazard Class	None Allocated	None Allocated	None Allocated
14.4 Packing Group	None Allocated	None Allocated	None Allocated

14.5 Environmental hazards No information provided

14.6 Special precautions for user

Hazchem code None Allocated



15. REGULATORY INFORMATION

15.1 Safety, health a	nd environmental regulations/legislation specific for the substance or mixture	
Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).	
Classifications	Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.	
	The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].	
Hazard codes	None allocated.	
Risk phrases	None allocated.	
Safety phrases	None allocated.	
Inventory listing(s)	AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.	

16. OTHER INFORMATION

Additional information ACRYLIC - WATER BASED COMPOUNDS: It should be noted that most water based paints and acrylic or thermoplastic resins may contain small percentage of solvents, usually less than 5%. The solvent is used as a dispersion agent for the resin of choice. This solvent component may present potential respiratory hazards only in poorly ventilated areas or when sprayed. Those individuals with existing skin disorders should avoid direct contact.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.



PRODUCT NAME RAPIDFIX LIQUID

Abbreviations	ACGIH	American Conference of Governmental Industrial Hygienists	
	CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds	
	CNS	Central Nervous System	
	EC No.	EC No - European Community Number	
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)	
	GHS	Globally Harmonized System	
	GTEPG	Group Text Emergency Procedure Guide	
	IARC	International Agency for Research on Cancer	
	LC50	Lethal Concentration, 50% / Median Lethal Concentration	
	LD50	Lethal Dose, 50% / Median Lethal Dose	
	mg/m ³	Milligrams per Cubic Metre	
	OEL	Occupational Exposure Limit	
	рН	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).	
	ppm	Parts Per Million	
	STEL	Short-Term Exposure Limit	
	STOT-RE	Specific target organ toxicity (repeated exposure)	
	STOT-SE	Specific target organ toxicity (single exposure)	
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons	
	SWA	Safe Work Australia	
	TLV	Threshold Limit Value	
	TWA	Time Weighted Average	
Report status		nt has been compiled by RMT on behalf of the manufacturer, importer or supplier of the erves as their Safety Data Sheet ('SDS').	
	manufacturer, the current sta at the time of	on information concerning the product which has been provided to RMT by the importer or supplier or obtained from third party sources and is believed to represent ate of knowledge as to the appropriate safety and handling precautions for the product f issue. Further clarification regarding any aspect of the product should be obtained he manufacturer, importer or supplier.	
	While RMT ha	as taken all due care to include accurate and up-to-date information in this SDS, it does	
	not provide an no liability for	ny warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts any loss, injury or damage (including consequential loss) which may be suffered or by person as a consequence of their reliance on the information contained in this SDS.	
Prepared by	5 Ventnor Äve		
	Western Australia 6005 Phone: +61 8 9322 1711		
	Fax: +61 8 9322 1794		
	Email: info@rmt.com.au		
	Web: www.rm	t.com.au.	
		[End of SDS]	



SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name RAPIDFIX GREY

Synonym(s) DRIBOND RAPIDFIX GREY

1.2 Uses and uses advised against

Use(s) ADHESIVE • ADHESIVE - CEMENTITIOUS

1.3 Details of the supplier of the product

Supplier name	DRIBOND CONSTRUCTION CHEMICALS	
Address	49-57 Davis Street, Wingfield, SA, 5013, AUSTRALIA	
Telephone	(08) 8243 7888	
Fax	(08) 8243 7800	
Email	info@constructionchemicals.com.au	
Website	www.constructionchemicals.com.au	

1.4 Emergency telephone number(s)

Emergency (08) 8243 7888

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

WARNING

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS classification(s) Skin Corrosion/Irritation: Category 2 Serious Eye Damage / Eye Irritation: Category 2A Specific Target Organ Systemic Toxicity (Single Exposure): Category 3 Specific Target Organ Systemic Toxicity (Repeated Exposure): Category 2

2.2	Label	elements

Signal word

Pictogram(s)



Hazard statement(s)

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Prevention statement(s)

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

PRODUCT NAME RAPIDFIX GREY

Response statement(s)	
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment is advised - see first aid instructions.
P332 + P337 + P313	If skin or eye irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before re-use.
Storage statement(s)	
P403 + P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal statement(s)	
P501	Dispose of contents/container in accordance with relevant regulations.
2.3 Other hazards	

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
ADDITIVE(S)	-	-	Remainder
CALCIUM ALUMINATE CEMENT	65997-16-2	266-045-5	30 to 60%
QUARTZ (CRYSTALLINE SILICA)	14808-60-7	238-878-4	1 to 10%
PORTLAND CEMENT	65997-15-1	266-043-4	<5%
CALCIUM SULPHATE HEMIHYDRATE	26499-65-0	607-950-0	1 to 10%

4. FIRST AID MEASURES

4.1 Description of first aid measures

EyeIf in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to
stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.InhalationIf inhaled, remove from contaminated area. Apply artificial respiration if not breathing.SkinIf skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.
Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

First aid facilities Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to the eyes, skin and respiratory system. Chronic over exposure to silica quartz dust may result in silicosis (lung disease). Principal symptoms of silicosis are coughing and breathlessness. Some individuals may exhibit an allergic response upon exposure to this product, possibly due to the trace amounts of chromium present. Crystalline silica and hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1).

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases if strongly heated.

5.3 Advice for firefighters

No fire or explosion hazard exists.



5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then collect and place in suitable containers for reuse or disposal. Avoid generating dust.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from moisture, incompatible substances and foodstuffs. Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
ingreatent	Reference	ppm	mg/m³	ppm	mg/m³
Portland Cement	SWA (AUS)		10		
Quartz (respirable dust)	SWA (AUS)		0.1		

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.

PPE

Eye / Face	Wear dust-proof goggles.
Hands	Wear PVC or rubber gloves.
Body	When using large quantities or where heavy contamination is likely, wear coveralls.
Respiratory	Where an inhalation risk exists, wear a Class P1 (Particulate) respirator. At high dust levels, wear an Air-line respirator or a Full-face Class P3 (Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	LIGHT COLOURED POWDER
Odour	SLIGHT ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
рН	11 (1% solution)
Vapour density	NOT AVAILABLE
Specific gravity	NOT AVAILABLE
Solubility (water)	SLIGHTLY SOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride). Water contact may increase product temperature 2°C to 3°C.

10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.
Skin	Irritating to the skin. Contact with powder or wetted form may result in irritation, rash and dermatitis.
Еуе	Irritating to the eyes. Contact may result in irritation, lacrimation, pain, redness, corneal burns and possible permanent damage.
Sensitisation	Not classified as causing respiratory sensitisation. However, some individuals may exhibit an allergic response upon exposure to cement, possibly due to trace amounts of chromium.
Mutagenicity	Insufficient data available to classify as a mutagen.
Carcinogenicity	This product contains crystalline silica and trace amounts of hexavalent chromium compounds which are classified as carcinogenic to humans (IARC Group 1). However, there is sufficient information to conclude that the relative risk of lung cancer from exposure to crystalline silica is increased in persons with silicosis. Therefore preventing the onset of silicosis will also reduce the cancer risk.
Reproductive	Insufficient data available to classify as a reproductive toxin.
STOT – single	Irritating to the respiratory system. Over exposure may result in irritation of the nose and throat, with

PRODUCT NAME **RAPIDFIX GREY**

exposure coughing. High level exposure may result in breathing difficulties.

Repeated exposure to respirable silica may result in pulmonary fibrosis (silicosis). Silicosis is a fibronodular STOT - repeated lung disease caused by deposition in the lungs of fine respirable particles of crystalline silica. Principal exposure symptoms of silicosis are coughing and breathlessness. In the wet state, the likelihood of an inhalation hazard is reduced.

Aspiration This product is a solid and aspiration hazards are not expected to occur.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal

Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information (if required).

Dispose of in accordance with relevant local legislation. Legislation

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

No information provided.

14.6 Special precautions for user

Hazchem code None allocated.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

A poison schedule number has not been allocated to this product using the criteria in the Standard for the **Poison schedule** Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

> The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

PRODUCT NAME	RAPIDFIX GREY		
Hazard codes	Xi Xn	Irritant Harmful	
Risk phrases	R36/37/38 R48/20	Irritating to eyes, respiratory system and skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation.	
Safety phrases	S22 S24/25 S26 S28 S36/37/39	Do not breathe dust. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice After contact with skin, wash immediately with plenty of water. Wear suitable protective clothing, gloves and eye/face protection.	
Inventory listing(s)		AUSTRALIA: AICS (Australian Inventory of Chemical Substances) All components are listed on AICS, or are exempt.	

16. OTHER INFORMATION

Additional information CEMENT CONTACT DERMATITIS: Individuals using wet cement, mortar, grout or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked or blistering skin with the potential for sensitisation. The dermatitis is due to the presence of soluble (hexavalent) chromium.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.



PRODUCT NAME RAPIDFIX GREY

Abbreviations	ACGIH CAS # CNS EC No.	American Conference of Governmental Industrial Hygienists Chemical Abstract Service number - used to uniquely identify chemical compounds Central Nervous System EC No - European Community Number
	EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
	GHS	Globally Harmonized System
	GTEPG	Group Text Emergency Procedure Guide
	IARC	International Agency for Research on Cancer
	LC50	Lethal Concentration, 50% / Median Lethal Concentration
	LD50	Lethal Dose, 50% / Median Lethal Dose
	mg/m³	Milligrams per Cubic Metre
	OEL	Occupational Exposure Limit
	рН	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
	ppm	Parts Per Million
	STEL	Short-Term Exposure Limit
	STOT-RE	Specific target organ toxicity (repeated exposure)
		Specific target organ toxicity (single exposure)
	SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
	SWA	Safe Work Australia
	TLV	Threshold Limit Value
	TWA	Time Weighted Average
Report status		t has been compiled by RMT on behalf of the manufacturer, importer or supplier of the erves as their Safety Data Sheet ('SDS').
manufacturer, importer or supplier or obtained from third party sources and is b the current state of knowledge as to the appropriate safety and handling precau		on information concerning the product which has been provided to RMT by the importer or supplier or obtained from third party sources and is believed to represent ate of knowledge as to the appropriate safety and handling precautions for the product f issue. Further clarification regarding any aspect of the product should be obtained he manufacturer, importer or supplier.
	not provide an no liability for	as taken all due care to include accurate and up-to-date information in this SDS, it does ny warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts any loss, injury or damage (including consequential loss) which may be suffered or ny person as a consequence of their reliance on the information contained in this SDS.
Prepared by	Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au.	
		[End of SDS]

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name RAPIDFIX WHITE

Synonym(s) DRIBOND RAPIDFIX WHITE

1.2 Uses and uses advised against

Use(s) ADHESIVE • ADHESIVE - CEMENTITIOUS

1.3 Details of the supplier of the product

Supplier name	DRIBOND CONSTRUCTION CHEMICALS
Address	49-57 Davis Street, Wingfield, SA, 5013, AUSTRALIA
Telephone	(08) 8243 7888
Fax	(08) 8243 7800
Email	info@constructionchemicals.com.au
Website	www.constructionchemicals.com.au

1.4 Emergency telephone number(s)

Emergency (08) 8243 7888

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

WARNING

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS classification(s) Skin Corrosion/Irritation: Category 2 Serious Eye Damage / Eye Irritation: Category 2A Specific Target Organ Systemic Toxicity (Single Exposure): Category 3 Specific Target Organ Systemic Toxicity (Repeated Exposure): Category 2

2.2	Label	elements

Signal word

Pictogram(s)



Hazard statement(s)

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Prevention statement(s)

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

PRODUCT NAME RAPIDFIX WHITE

Response statement(s)	
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment is advised - see first aid instructions.
P332 + P337 + P313	If skin or eye irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before re-use.
Storage statement(s)	
P403 + P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal statement(s)	
P501	Dispose of contents/container in accordance with relevant regulations.
2.3 Other hazards	

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
ADDITIVE(S)	-	-	Remainder
CALCIUM ALUMINATE CEMENT	65997-16-2	266-045-5	30 to 60%
QUARTZ (CRYSTALLINE SILICA)	14808-60-7	238-878-4	1 to 10%
PORTLAND CEMENT	65997-15-1	266-043-4	<5%
CALCIUM SULPHATE HEMIHYDRATE	26499-65-0	607-950-0	1 to 10%

4. FIRST AID MEASURES

4.1 Description of first aid measures

EyeIf in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to
stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.InhalationIf inhaled, remove from contaminated area. Apply artificial respiration if not breathing.SkinIf skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

First aid facilities Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to the eyes, skin and respiratory system. Chronic over exposure to silica quartz dust may result in silicosis (lung disease). Principal symptoms of silicosis are coughing and breathlessness. Some individuals may exhibit an allergic response upon exposure to this product, possibly due to the trace amounts of chromium present. Crystalline silica and hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1).

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases if strongly heated.

5.3 Advice for firefighters

No fire or explosion hazard exists.



5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then collect and place in suitable containers for reuse or disposal. Avoid generating dust.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from moisture, incompatible substances and foodstuffs. Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
ingreatent	Kelefence		mg/m³	ppm	mg/m³
Portland Cement	SWA (AUS)		10		
Quartz (respirable dust)	SWA (AUS)		0.1		

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.

PPE

Eye / Face	Wear dust-proof goggles.
Hands	Wear PVC or rubber gloves.
Body	When using large quantities or where heavy contamination is likely, wear coveralls.
Respiratory	Where an inhalation risk exists, wear a Class P1 (Particulate) respirator. At high dust levels, wear an Air-line respirator or a Full-face Class P3 (Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	LIGHT COLOURED POWDER
Odour	SLIGHT ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
рН	11 (1% solution)
Vapour density	NOT AVAILABLE
Specific gravity	NOT AVAILABLE
Solubility (water)	SLIGHTLY SOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride). Water contact may increase product temperature 2°C to 3°C.

10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.
Skin	Irritating to the skin. Contact with powder or wetted form may result in irritation, rash and dermatitis.
Еуе	Irritating to the eyes. Contact may result in irritation, lacrimation, pain, redness, corneal burns and possible permanent damage.
Sensitisation	Not classified as causing respiratory sensitisation. However, some individuals may exhibit an allergic response upon exposure to cement, possibly due to trace amounts of chromium.
Mutagenicity	Insufficient data available to classify as a mutagen.
Carcinogenicity	This product contains crystalline silica and trace amounts of hexavalent chromium compounds which are classified as carcinogenic to humans (IARC Group 1). However, there is sufficient information to conclude that the relative risk of lung cancer from exposure to crystalline silica is increased in persons with silicosis. Therefore preventing the onset of silicosis will also reduce the cancer risk.
Reproductive	Insufficient data available to classify as a reproductive toxin.
STOT – single	Irritating to the respiratory system. Over exposure may result in irritation of the nose and throat, with

PRODUCT NAME **RAPIDFIX WHITE**

exposure coughing. High level exposure may result in breathing difficulties.

Repeated exposure to respirable silica may result in pulmonary fibrosis (silicosis). Silicosis is a fibronodular STOT - repeated lung disease caused by deposition in the lungs of fine respirable particles of crystalline silica. Principal exposure symptoms of silicosis are coughing and breathlessness. In the wet state, the likelihood of an inhalation hazard is reduced.

Aspiration This product is a solid and aspiration hazards are not expected to occur.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal

Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information (if required).

Dispose of in accordance with relevant local legislation. Legislation

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

No information provided.

14.6 Special precautions for user

Hazchem code None allocated.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

A poison schedule number has not been allocated to this product using the criteria in the Standard for the **Poison schedule** Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

> The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

PRODUCT NAME	RAPIDFIX WHITE		
Hazard codes	Xi Xn	Irritant Harmful	
Risk phrases	R36/37/38 R48/20	Irritating to eyes, respiratory system and skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation.	
Safety phrases	S22 S24/25 S26 S28 S36/37/39	Do not breathe dust. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice After contact with skin, wash immediately with plenty of water. Wear suitable protective clothing, gloves and eye/face protection.	
Inventory listing(s)		: AICS (Australian Inventory of Chemical Substances) ts are listed on AICS, or are exempt.	

16. OTHER INFORMATION

Additional information CEMENT CONTACT DERMATITIS: Individuals using wet cement, mortar, grout or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked or blistering skin with the potential for sensitisation. The dermatitis is due to the presence of soluble (hexavalent) chromium.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.



PRODUCT NAME **RAPIDFIX WHITE**

Abbreviations	ACGIH CAS # CNS EC No. EMS	American Conference of Governmental Industrial Hygienists Chemical Abstract Service number - used to uniquely identify chemical compounds Central Nervous System EC No - European Community Number Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous
	GHS GTEPG IARC LC50 LD50 mg/m ³ OEL pH STEL STOT-RE STOT-RE STOT-SE SUSMP SWA TLV TWA	Goods) Globally Harmonized System Group Text Emergency Procedure Guide International Agency for Research on Cancer Lethal Concentration, 50% / Median Lethal Concentration Lethal Dose, 50% / Median Lethal Dose Milligrams per Cubic Metre Occupational Exposure Limit relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). Parts Per Million Short-Term Exposure Limit Specific target organ toxicity (repeated exposure) Specific target organ toxicity (single exposure) Standard for the Uniform Scheduling of Medicines and Poisons Safe Work Australia Threshold Limit Value Time Weighted Average
		nt has been compiled by RMT on behalf of the manufacturer, importer or supplier of the erves as their Safety Data Sheet ('SDS').
	manufacturer, the current sta at the time of	on information concerning the product which has been provided to RMT by the importer or supplier or obtained from third party sources and is believed to represent ate of knowledge as to the appropriate safety and handling precautions for the product f issue. Further clarification regarding any aspect of the product should be obtained he manufacturer, importer or supplier.
	not provide an no liability for	as taken all due care to include accurate and up-to-date information in this SDS, it does ny warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts any loss, injury or damage (including consequential loss) which may be suffered or ny person as a consequence of their reliance on the information contained in this SDS.
Prepared by	Risk Manager 5 Ventnor Ave Western Austr Phone: +61 8 Fax: +61 8 93 Email: info@ri Web: www.rm	ralia 6005 9322 1711 22 1794 mt.com.au
		[End of SDS]