

# SAFETY DATA SHEET

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

### 1.1 Product identifier

**Product name** REINFORCED SCREED  
**Synonyms** DRIBOND FLOOR / REINFORCED SCREED

### 1.2 Uses and uses advised against

**Uses** CEMENT

### 1.3 Details of the supplier of the product

**Supplier name** MANUFACTURER: DRIBOND CONSTRUCTION CHEMICALS  
**Address** 49-57 Davis Street, Wingfield, SA, 5013, AUSTRALIA  
**Telephone** (08) 8243 7888  
**Fax** (08) 8243 7800  
**Email** [info@constructionchemicals.com.au](mailto:info@constructionchemicals.com.au)  
**Website** [www.constructionchemicals.com.au](http://www.constructionchemicals.com.au)

### 1.4 Emergency telephone numbers

**Emergency** (08) 8243 7888

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

#### Physical Hazards

Not classified as a Physical Hazard

#### Health Hazards

Skin Corrosion/Irritation: Category 2  
Serious Eye Damage / Eye Irritation: Category 2A  
Specific Target Organ Toxicity (Single Exposure): Category 3 (Respiratory Irritation)

#### Environmental Hazards

Not classified as an Environmental Hazard

### 2.2 GHS Label elements

**Signal word** WARNING

#### Pictograms



#### Hazard statements

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.

## PRODUCT NAME REINFORCED SCREED

### Prevention statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

### Response statements

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P321	Specific treatment is advised - see first aid instructions.
P332 + P337 + P313	If skin or eye irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before re-use.

### Storage statements

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

### Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

### 2.3 Other hazards

No information provided.

---

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

---

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
ADDITIVE(S)	-	-	Remainder
GYPSUM	13397-24-5	603-783-2	Not Available
CALCIUM ALUMINATE CEMENT	-	-	10 to 30%
FILLER(S)	-	-	Not Available
SAND, AMORPHOUS	-	-	Not Available

---

## 4. FIRST AID MEASURES

---

### 4.1 Description of first aid measures

<b>Eye</b>	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
<b>Ingestion</b>	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
<b>First aid facilities</b>	Eye wash facilities and safety shower should be available.

### 4.2 Most important symptoms and effects, both acute and delayed

Irritating to the eyes, skin and respiratory system. Some Individuals may exhibit an allergic response upon exposure to this product, possibly due to the trace amounts of chromium present. Hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1).

### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

---

## 5. FIRE FIGHTING MEASURES

---

### 5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

## PRODUCT NAME REINFORCED SCREED

### 5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases if strongly heated.

### 5.3 Advice for firefighters

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

### 5.4 Hazchem code

None allocated.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Contact emergency services where appropriate.

### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

### 6.3 Methods of cleaning up

Contain spillage, then collect and place in suitable containers for reuse or disposal. Avoid generating dust.

### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

---

## 7. HANDLING AND STORAGE

---

### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from moisture, incompatible substances and foodstuffs. Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.

### 7.3 Specific end uses

No information provided.

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Gypsum (Calcium sulphate)	SWA [AUS]	--	10	--	--

#### Biological limits

No biological limit values have been entered for this product.

### 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.

## PRODUCT NAME REINFORCED SCREED

### PPE

<b>Eye / Face</b>	Wear dust-proof goggles.
<b>Hands</b>	Wear PVC or rubber gloves.
<b>Body</b>	When using large quantities or where heavy contamination is likely, wear coveralls.
<b>Respiratory</b>	Where an inhalation risk exists, wear a Class P1 (Particulate) respirator. At high dust levels, wear an Air-line respirator or a Full-face Class P3 (Particulate) respirator.



---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

<b>Appearance</b>	DARK COLOURED POWDER
<b>Odour</b>	ODOURLESS
<b>Flammability</b>	NON FLAMMABLE
<b>Flash point</b>	NOT RELEVANT
<b>Boiling point</b>	NOT AVAILABLE
<b>Melting point</b>	NOT AVAILABLE
<b>Evaporation rate</b>	NOT AVAILABLE
<b>pH</b>	11 (1% solution)
<b>Vapour density</b>	NOT AVAILABLE
<b>Relative density</b>	3
<b>Solubility (water)</b>	SLIGHTLY SOLUBLE
<b>Vapour pressure</b>	NOT AVAILABLE
<b>Upper explosion limit</b>	NOT RELEVANT
<b>Lower explosion limit</b>	NOT RELEVANT
<b>Partition coefficient</b>	NOT AVAILABLE
<b>Autoignition temperature</b>	NOT AVAILABLE
<b>Decomposition temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	NOT AVAILABLE
<b>Explosive properties</b>	NOT AVAILABLE
<b>Oxidising properties</b>	NOT AVAILABLE
<b>Odour threshold</b>	NOT AVAILABLE

---

## 10. STABILITY AND REACTIVITY

---

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

### 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride). Water contact may increase product temperature 2°C to 3°C.

### 10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

---

## 11. TOXICOLOGICAL INFORMATION

---

**PRODUCT NAME REINFORCED SCREED**

**11.1 Information on toxicological effects**

<b>Acute toxicity</b>	Based on available data, the classification criteria are not met.
<b>Skin</b>	Irritating to the skin. Contact with powder or wetted form may result in irritation, rash and dermatitis.
<b>Eye</b>	Causes serious eye damage. Contact with moisture in the eyes may result in irritation, lacrimation, pain, redness, conjunctivitis and possible alkaline burns aided by mechanical irritation and abrasion.
<b>Sensitisation</b>	Not classified as causing respiratory sensitisation. However, some individuals may exhibit an allergic response upon exposure to cement, possibly due to trace amounts of chromium.
<b>Mutagenicity</b>	Insufficient data available to classify as a mutagen.
<b>Carcinogenicity</b>	Hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1), however due to the trace amounts present, the criteria for classification is not met.
<b>Reproductive</b>	Insufficient data available to classify as a reproductive toxin.
<b>STOT - single exposure</b>	Irritating to the respiratory system. Over exposure may result in irritation of the nose and throat, with coughing. High level exposure may result in breathing difficulties.
<b>STOT - repeated exposure</b>	Repeated exposure may effect the respiratory system resulting inflammation of the lungs due to irritation caused by the inhalation of dust.
<b>Aspiration</b>	This product is a solid and aspiration hazards are not expected to occur.

---

**12. ECOLOGICAL INFORMATION**

---

**12.1 Toxicity**

No information provided.

**12.2 Persistence and degradability**

No information provided.

**12.3 Bioaccumulative potential**

No information provided.

**12.4 Mobility in soil**

No information provided.

**12.5 Other adverse effects**

No information provided.

---

**13. DISPOSAL CONSIDERATIONS**

---

**13.1 Waste treatment methods**

<b>Waste disposal</b>	Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information (if required).
<b>Legislation</b>	Dispose of in accordance with relevant local legislation.

---

**14. TRANSPORT INFORMATION**

---

**NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA**

	<b>LAND TRANSPORT (ADG)</b>	<b>SEA TRANSPORT (IMDG / IMO)</b>	<b>AIR TRANSPORT (IATA / ICAO)</b>
<b>14.1 UN Number</b>	None allocated.	None allocated.	None allocated.
<b>14.2 Proper Shipping Name</b>	None allocated.	None allocated.	None allocated.
<b>14.3 Transport hazard class</b>	None allocated.	None allocated.	None allocated.
<b>14.4 Packing Group</b>	None allocated.	None allocated.	None allocated.

**14.5 Environmental hazards**

No information provided.

**14.6 Special precautions for user**

**Hazchem code** None allocated.

## 15. REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>Poison schedule</b>	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
<b>Classifications</b>	Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.
<b>Inventory listings</b>	<b>AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)</b> All components are listed on AIIC, or are exempt.

## 16. OTHER INFORMATION

**Additional information**      **RESPIRATORS:** In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

**CEMENT CONTACT DERMATITIS -** Individuals using wet cement, mortar, grout or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked or blistering skin with the potential for sensitisation. The dermatitis is due to the presence of soluble (hexavalent) chromium.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

### Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**PRODUCT NAME REINFORCED SCREED**

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**