

Adhering Moisture Sensitive Stone/Tiles

Sealing Tiles

Kemcote

Packaging Mixing



Application



Substrates

Concrete
Terrazzo
Stone, Tiles
Marble
Granite

Adhesive

Packaging



Mixing Required

Application



Substrates

Concrete
Screed
Cement sheeting

Grouting

Packaging



Mixing Required

Application



Substrates

Stone, Tiles
Marble
Granite

Materials

Kemcote (solvent-based, acrylic water repellent), **Ultima** (two-pack, white, flexible tile adhesive), **Monoflex** (one-pack, polymer-modified, cement-based adhesive), **Rapidfix** (two-pack, fast-set, ceramic tile adhesive), **Kemgrout** (cement-based, flexible grout), **Primebond** (acrylic bonding liquid), **Primax** (water-resistant, acrylic primer).

Surface Preparation

Surface must be clean and structurally sound, free from grease, dust, coatings and other contaminants. New concrete must be 28 days old.

Workmanship

Apply product in accordance with the manufacturer's written instructions, good trade practice and local codes.

Application

Sealing the moisture sensitive stone – when using **Monoflex** or **Ultima**. Brush two coats of **Kemcote** to the back and the sides of stone/tile. Allow to dry 2-3 hours before fixing. **Pre-sealing not required when using Rapidfix.**

Adhesive

Apply either the **Monoflex** (off-white colour), **Ultima** (colour - white) or **Rapidfix** (colour - grey or white) using the colour adhesive that is appropriate to the stone/tile.

Grouting

Mix **Primebond** with the **Kemgrout** to a thick, creamy consistency and grout the joints.

