

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name MIGHTYMASTIC
Synonyms DRIBOND MIGHTY MASTIC

1.2 Uses and uses advised against

Uses ADHESIVE • TILE ADHESIVE

1.3 Details of the supplier of the product

Manufacturer name DRIBOND CONSTRUCTION CHEMICALS
Address 49-57 Davis Street, Wingfield, SA, 5013, AUSTRALIA
Telephone (08) 8243 7888
Fax (08) 8243 7800
Email info@constructionchemicals.com.au
Website www.constructionchemicals.com.au

1.4 Emergency telephone numbers

Emergency (08) 8243 7888

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Physical Hazards

Not classified as a Physical Hazard

Health Hazards

Skin Corrosion/Irritation: Category 2A
Serious Eye Damage / Eye Irritation: Category 1
Specific Target Organ Toxicity (Single Exposure): Category 3 (Respiratory Irritation)

Environmental Hazards

Not classified as an Environmental Hazard

2.2 GHS Label elements

Signal word WARNING

Pictograms



Hazard statements

H315 Causes skin irritation.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

Prevention statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

PRODUCT NAME MIGHTYMASTIC**Response statements**

P302 + P352	IF ON SKIN: Wash with plenty of water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P321	Specific treatment is advised - see first aid instructions.
P332 + P337 + P313	If skin or eye irritation occurs: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Storage statements

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Disposal statements

P501	Dispose of contents/container in accordance with relevant regulations.
------	--

2.3 Other hazards

Some susceptible individuals may exhibit an allergic skin response upon exposure to portland cement, possibly due to trace amounts of chromium.

Prolonged exposure to portland cement in the wet form can cause serious, potentially irreversible skin or eye damage in the form of chemical burns. The same serious injury can occur if wet or moist skin or eyes have prolonged contact exposure to dry portland cement.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
PORTLAND CEMENT	65997-15-1	266-043-4	30 to 60%
ADDITIVE(S)	-	-	Remainder

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
First aid facilities	Eye wash facilities and safety shower should be available.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to the eyes, skin and respiratory system. Some Individuals may exhibit an allergic response upon exposure to this product, possibly due to the trace amounts of chromium present. Hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1).

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

Non flammable. May evolve toxic gases if strongly heated.

5.3 Advice for firefighters

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then collect and place in suitable containers for reuse or disposal. Avoid generating dust.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from moisture, incompatible substances and foodstuffs. Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.

7.3 Specific end uses

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters**Exposure standards**

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Portland cement	SWA [AUS]	--	10	--	--
Portland cement	SWA [Proposed]	--	1	--	--

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended. Maintain dust levels below the recommended exposure standard.

PPE

Eye / Face	Wear dust-proof goggles.
Hands	Wear PVC or rubber gloves.
Body	When using large quantities or where heavy contamination is likely, wear coveralls.
Respiratory	Where an inhalation risk exists, wear a Class P1 (Particulate) respirator. At high dust levels, wear an Air-line respirator or a Full-face Class P3 (Particulate) respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	COLOURED POWDER
Odour	SLIGHT ODOUR
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	11 (1% solution)
Vapour density	NOT AVAILABLE
Relative density	NOT AVAILABLE
Solubility (water)	SLIGHTLY SOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride). Water contact may increase product temperature 2°C to 3°C.

10.6 Hazardous decomposition products

May evolve toxic gases if heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	Acute oral exposure may result in irritation of the mouth, throat, oesophagus and gastrointestinal tract.
Skin	Irritating to the skin. Contact with powder or wetted form may result in irritation, rash and dermatitis.
Eye	Contact with moisture in the eyes may result in irritation, lacrimation, pain, redness, conjunctivitis and possible alkaline burns aided by mechanical irritation and abrasion.
Sensitisation	Not classified as causing respiratory sensitisation. However, some individuals may exhibit an allergic response upon exposure to cement, possibly due to trace amounts of chromium.
Mutagenicity	Insufficient data available to classify as a mutagen.
Carcinogenicity	Hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1), however due to the trace amounts present, the criteria for classification is not met.
Reproductive	Insufficient data available to classify as a reproductive toxin.
STOT - single exposure	Irritating to the respiratory system. Over exposure may result in irritation of the nose and throat, with coughing. High level exposure may result in breathing difficulties.
STOT - repeated exposure	Repeated exposure may effect the respiratory system resulting inflammation of the lungs due to irritation caused by the inhalation of dust.
Aspiration	This product is a solid and aspiration hazards are not expected to occur.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal	Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information (if required).
Legislation	Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None allocated.	None allocated.	None allocated.
14.2 Proper Shipping Name	None allocated.	None allocated.	None allocated.
14.3 Transport hazard class	None allocated.	None allocated.	None allocated.
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

Not a Marine Pollutant.

14.6 Special precautions for user

Hazchem code None allocated.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Classifications	Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).
Inventory listings	AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals) All components are listed on AIIC, or are exempt.

16. OTHER INFORMATION

Additional information	RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary. CEMENT CONTACT DERMATITIS -Individuals using wet cement, mortar, grout or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked or blistering skin with the potential for sensitisation. The dermatitis is due to the presence of soluble (hexavalent) chromium. PERSONAL PROTECTIVE EQUIPMENT GUIDELINES: The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made. HEALTH EFFECTS FROM EXPOSURE: It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.
-------------------------------	--

Abbreviations	ACGIH American Conference of Governmental Industrial Hygienists CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds CNS Central Nervous System EC No. European Community Number EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods) GHS Globally Harmonized System GTEPG Group Text Emergency Procedure Guide IARC International Agency for Research on Cancer LC50 Lethal Concentration, 50% / Median Lethal Concentration LD50 Lethal Dose, 50% / Median Lethal Dose mg/m³ Milligrams per Cubic Metre OEL Occupational Exposure Limit pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). ppm Parts Per Million STEL Short-Term Exposure Limit STOT-RE Specific target organ toxicity (repeated exposure) STOT-SE Specific target organ toxicity (single exposure) SUSMP Standard for the Uniform Scheduling of Medicines and Poisons SWA Safe Work Australia TLV Threshold Limit Value TWA Time Weighted Average
----------------------	---

[End of SDS]