

EPEGROUT	EPEGROUT TRADE	EPEGROUT ULTRA	KEMGROUT FLEXIBLE	KEMGROUT SANDED	
			●		Wall and floor fine finish flexible coloured grout for joints up to 5mm
				●	Wall and floor coloured grout for joints 2mm-10mm
●					Hygienic chemical resistant grout for commercial areas (for joints up to 3mm)
	●				Hygienic chemical resistant grout for commercial areas (for joints 2mm - 10mm)
		●			Easy clean off, solvent-free, pool grade and hygienic chemical resistant grout for commercial areas (for joints 1.5mm - 10mm)

GROUT SHIELD

A water-based, silicone sealer for sanded and fine grouts that repels water and shields the grout from contaminants and staining. For use on exterior and interior floors and walls. Does not change the appearance of the grout.

PRIMEBOND

An acrylic-based, liquid additive for **Kemgrout** to increase the strength, mould resistance and reduce grout staining and discolouration.

Amount of grout required in Kg/m ²				Always allow 10% for wastage. Estimate only - site coverage may vary.				
Tile Size (mm) Length x Width x Depth	Joint width			Tile Size (mm) Length x Width x Depth	Joint Width			
	1.5mm	3mm	5mm		6mm	8mm	10mm	
25 x 25 x 4	0.55	1.00	1.55	200 x 200 x 13	1.06	1.30	1.60	
50 x 50 x 6	0.40	0.80	1.30	250 x 250 x 10	0.77	1.02	1.30	
100 x 100 x 8	0.30	0.60	0.90	300 x 300 x 10	0.65	0.86	1.06	
200 x 200 x 8	0.14	0.28	0.48	330 x 330 x 10	0.60	0.78	0.97	
200 x 250 x 7	0.13	0.26	0.42	400 x 400 x 12	0.58	0.78	1.00	
330 x 330 x 9	0.11	0.22	0.36	450 x 450 x 12	0.52	0.69	0.86	
330 x 250 x 9	0.13	0.25	0.41	500 x 500 x 12	0.47	0.62	0.78	
400 x 400 x 10	0.09	0.18	0.30	600 x 300 x 12	0.60	0.77	1.00	
450 x 450 x 10	0.08	0.16	0.26	600 x 600 x 12	0.40	0.60	0.80	
600 x 600 x 10	0.06	0.12	0.20					

Add 30% to these volumes for Kemgrout Sanded and Epegrout. Check website calculator for other sizes.

User must always refer to constructionchemicals.com.au for the latest technical data sheet for the product concerned.

- Adelaide
- Brisbane
- Melbourne
- Perth
- Sydney
- Auckland
- Kuala Lumpur

