

FLOORING PREPARATION

Priming, patching and levelling products for the preparation of tiled floors in commercial and domestic applications.



ELASTABOND

Resin dispersion to fortify cement flooring compounds. Use in place of mixing water.

Features

Improves the elasticity, bond strength and abrasion resistance when added to levelling/repair compounds to:

- Level rigid timber floors
- Repair heavily walked/trafficked areas i.e. stair treads
- Add to levelling compound before overcoating flexible flooring systems
- Cover underfloor heating with screeds or levelling compounds



EPECRETE

Multipurpose, water-based, epoxy moisture barrier.

Coverage - 3kg kit
Dampproofing: 9m² (2 coats)
Primer: 18m² (1 coat)

Features

- Stops moisture and dampness penetrating through masonry floors and walls
- Does not impair the adhesion of finishes and adhesives
- Long life – will perform for the life of the structure
- Easily mixed and applied
- Water based
- No priming required. Epecrete is both primer and coating



FEATHER FLOOR

Cement based, rapid-setting trowel-applied finishing underlay designed to smooth ridges, grooves, joints and gaps in the floor. Apply 0-3mm thick prior to installing a floor covering.

Coverage

15-30m²/5kg bag depending on the surface condition.

Features

- Exceptional bond strength
- No primer required
- Can be featheredged
- Rapid setting

FLOORING PREPARATION



LEVEL FLOOR STANDARD

Resin-modified, fast-setting, cement-based compound for use as an underlay and repair screed. Its smooth texture and high fluidity allow ease of placement, trowelling, featheredging and finish.

Coverage

1.5kg/m² per 1mm thickness

Features

- Apply featheredge to 50mm
- Water resistant
- Rapid set
- Low VOC



LEVEL FLOOR TUFF

Resin-modified, fast-setting, cement-based compound for use as a levelling compound and repair screed. Its smooth texture and high fluidity allow ease of placement, trowelling, featheredging and finish.

Coverage

1.5 kg/m² per 1mm thickness

Features

- Featheredge to 15mm thick
- Water resistant – rapid set



LEVEL FLOOR V15

Smooth, sandable, self-levelling underlay prior to laying carpet and vinyl.

Coverage

1.5kg/m² per 1mm thickness

Features

- Durable and crack resistant (40MPa)
- Self levelling: smooth float finish
- Rapid set – 2 to 4 hours
- Smooth finish and sandable
- Apply floor coverings in 15 hours
- Apply featheredge to 50mm
- Compatible with most adhesives



KEMCRETE

Acrylic, liquid-based admixture and primer for structurally sound concrete and mortar mixtures.

Coverage

Primer: 15m²/litre

Bonding Slurry: 3-4 m²/litre

Mortar Additive: 1m²/litre (10mm thick in a 3:1 sand/cement mix)

Features

- Primer
- Bonding slurry (Primax)
- Mortar additive
- Kemgrip additive



PATCH & ANCHOR

Fast-setting patching compound.

Coverage

15kg/m² at 6mm thickness

Features

- Develops very high strengths
- Non-shrink
- High bond strength to masonry surfaces, i.e. concrete, brick, block
- Very low water absorption when set
- Does not contain calcium chloride, therefore will not corrode anchor bolt and reinforcing steel
- Cement colour match



PRIMAX

Two-pack, water-resistant, bonding primer with exceptional adhesion to difficult to adhere to surfaces.

Coverage

5L/5kg covers 20m²

Features

- Eliminates the need to mechanically roughen or acid etch concrete
- Water resistant
- Ideal as a primer over ceramic tiles

FLOORING PREPARATION



RAPID SET 45


Fast-setting, non-slump, cement patching and repair compound.

Coverage

1.5kg/m² per 1mm thickness

Features

- Develops high strength
- Low shrinkage
- Good bond to masonry surfaces
- Sets in 1 hour



REINFORCED SCREED

Impact-resistant flooring compound.

Coverage

3mm - 5kg/m², 5mm - 8kg/m²

Features

- Strong, durable, crack resistant
- Can be featheredged
- Aggregate can be added when using over 5 mm thick
- Water resistant
- Fast setting - use within 6 hours
- Chemical resistant
- Temperature resistant
- Wear resistant – three times harder than concrete



SUPER PRIME

Water-based primer for non-porous surfaces.

Coverage

8-10m²/litre

Features

- Exceptional adhesion to smooth concrete
- Reduces air bubbles rising through levelling compounds
- Eliminates the need to etch or scabble concrete
- Has solvent like penetrating properties



CONCRETE HARDENER

Chemically hardens concrete floors.

Coverage

Allow at least 1 litre per 4m² per coat (two coats are required).

Features

- Easy to apply
- Permanently case hardens dusty or soft concrete or cement based structures by up to 300% of untreated concrete
- Dustproofs by bonding and strengthening the cement's crystalline structure
- Substantially increases chemical/abrasion resistance
- Seals the structure against moisture penetration



PRESTO

Liquid set accelerator for screeds and cement mixes. Use in place of mixing water.

Features

- Rapid set & high early strength
- 7 day strength is obtained in 48 hours
- Ready to use

Adelaide

49-57 Davis Street
Wingfield SA 5013
Phone (08) 8243 7888

Brisbane

45 Coulson Street
Wacol QLD 4076
Phone (07) 3271 2944

Melbourne

11 Gabrielle Court
Bayswater North VIC 3153
Phone (03) 9761 4711

Perth

11 Collie Street
Welshpool WA 6106
Phone (08) 9356 9999

Sydney

31-33 Newton Road
Wetherill Park NSW 2164
Phone (02) 9756 3533

Auckland

16 Carpenter Road
East Tamaki
Phone (09) 273 5444

Kuala Lumpur

Lot 2 Jalan Kecapi,
33/2 Elite Industrial Estate
Off Jalan Bukit Kemuning,
40000 Shah Alam
Phone (603) 5122 2522